

DWS5501-33-45

Specification

55" Display Wall Stand, 3x3 Landscape, 450nits, narrow bezel



Features

- 9.8mm Narrow Bezel Display Wall Stand
- Fit with Winsonic Display Wall Monitor x 9 pcs
- Easy Mounting Structure
- Cable Management solution

Spec of Stand

Monitor Arrangement	3 x 3 Landscape	
Resolution	5760 x 3240	
Dimension	Physical	3709.4 x 2582.15 x 1157 (mm)
	Carton	TBD
	N.W. / G.W.	TBD

Spec of LCD Monitor (for single unit)

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating	
	Aspect Ratio / Size	Wide / 55" viewable diagonal area	
	Active Area / Pixel Pitch	1209.6(H) x 680.4(V) mm / 0.21(H) x 0.63(V) mm	
	Native Resolution / Colors	1920(H) x 1080(V) / 1073.7 Million	
	Brightness / Contrast	450 cd/m ² (typ) / 4000 : 1	
	Response Time	≤ 6.5 ms (G-to-G)	
	Viewing Angle (typical)	H. 178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)	
	Light Source	LED, Long life, 50,000 hrs (typ)	
Input Sources	PC System	Signal	Analog RGB (0.7/1.0 V _{p-p} , 75 ohms)
			Digital (DVI-D)
		Sync	Separate Sync, Composite Sync, Sync On Green
	Frequency	F _n : 30 - 82Khz , F _v : 50 - 75Hz	
Input Terminals	1 x VGA (15 Pin Female D-Sub) , 1 x DVI, 1 x AC Inlet		
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)		
	OSD Multi-Languages		
Power	Internal power supply with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 Hz		
Power Consumption	Operation / Power Saving	150 watt , < 5 watt (Support DPMS)	
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)	
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)	
Certification	FCC , CE		
Dimensions	Physical	W x H x D : 1235.6 x 706.4 x 108.5 (mm)	
	Carton	W x H x D = TBD	
Weight	N.W. / G.W.	30.0 Kgs / 32.5 Kgs	

Option Model

DWS5501-33-70	55" Display Wall Stand, 3x3 Landscape, 700nits, narrow bezel
DWS5501-33-A0	55" Display Wall Stand, 3x3 Landscape, 1000nits, narrow bezel

Winsonic®

Winsonic Electronics CO.,LTD. TEL:886-3-3704789 FAX:886-3-3704722 E-mail:sales@ewinsonic.com
No.290-1 Wun-Jhong Rd. Taoyuan City, Taoyuan Taiwan R.O.C