

Fanless Panel PC Chassis, 18.5" LCD monitor, 1920 x 1080, LED 1000 nits, Intel® Celeron J1900



Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Celeron J1900
- Intel® Atom BayTrail
- Dual Channel DDR3 1333 MHz SDRAM, Max up to 8GB
- 1 x VGA, 1 x HDMI, 3 x COM, 2 x LAN, 2 x USB 2.0, 2 x USB 3.0

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 18.5" viewable diagonal area
	Active Area / Pixel Pitch	408.96(H) x 230.4(V) mm / 231(H) x 213(V) per one triad
	Native Resolution / Colors	1920(H) x 1080(V) / 16.7M
	Brightness / Contrast	1000 cd/m ² (typ) / 1000 : 1
	Response Time	≤ 20 ms
	Viewing Angle (typical)	H.178° (- 89° ~ + 89°) , V. 178°(- 89° ~ + 89°)
	Light Source	LED backlight, Long life, 35,000 hrs (typ)
System	CPU	Intel® Celeron J1900 Processor
	BIOS	UEFI
	System / Graphic Chipset	Intel® Gen7 Intel Graphics DX 11*, OGL3.2
	System Memory	Dual Channel DDR3 1333 MHz SDRAM, Max up to 8GB
	HDD	2 x SATA
	I/O port	1 x VGA, 1 x HDMI
		2 x USB 2.0, 2 x USB 3.0
3 x COM (RS232/422/485)		
2 x LAN, Mic-in, Line-out		
Expansion	1 x Mini PCI-e	
Power	Power Input	12V DC input with adapter
	Power Consumption	27.5 Watt, <1 Watt
Operating Condition	Temperature / Humidity	- 20°C ~ 70°C (- 4°F ~ 158°F) , 10% ~ 90% (no condensation)
Dimensions	Physical	Please refer to Drawing
	Carton	W x H x D = TBD

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	SAW touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Infrared touch		Sunlight Readable	Light Sensor
	Protected glass			Auto-Dimming