

Panel PC Open Frame, 15" LCD monitor, 1024 x 768, LED 250 nits, Intel® Core i3 / i5 / i7 Processors



## Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Core i3 / i5 / i7 Processors
- Intel® H110
- 2 x DDR4 SO-DIMM slots, up to 32GB 2133MHz
- 1 x HDMI, 1 x Display Port, 4 x USB 3.0, 2 x LAN

|                           |                            |   |
|---------------------------|----------------------------|---|
| Panel                     | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating          |
|                           | Aspect Ratio / Size        | 4 : 3 / 15" viewable diagonal area                          |
|                           | Active Area / Pixel Pitch  | 304.13(H) x 228.10(V) mm / 0.297(H) x 0.297(V) mm           |
|                           | Native Resolution / Colors | 1024(H) x 768(V) / 16.2 M                                   |
|                           | Brightness / Contrast      | 250 cd/m <sup>2</sup> (typ) / 700 : 1                       |
|                           | Response Time              | ≤ 35 ms   |
|                           | Viewing Angle (typical)    | H. 140° (- 70° ~ + 70°) , V. 120°(- 60° ~ + 60°)            |
|                           | Light Source               | LED backlight, Long life, 35,000 hrs (typ)                  |
| System                    | CPU                        | Support for Intel® Core i7 / i5 / i3 / Celeron® (Skylake-S) |
|                           | BIOS                       | UEFI  |
|                           | System / Graphic Chipset   | Intel® H110   |
|                           | System Memory              | 2 x DDR4 SO-DIMM slots, up to 32GB 2133MHz                  |
|                           | HDD                        | 4 x SATA2   |
|                           | I/O port                   | 1 x HDMI  |
|                           |                            | 4 x USB 3.0   |
| 1 x Display Port          |                            |   |
| 1 x LAN, Mic-in, Line-out |                            |   |
| Expansion                 | 1 x Mini PCI-e             |   |
| Power                     | Power Input                | 12V / 19~24V DC-in (DC Jack / 4-pin ATX PWR Con)            |
|                           | Power Consumption          | 65 Watt, <1 Watt  |
| Operating Condition       | Temperature / Humidity     | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)     |
| Dimensions                | Physical                   | Please refer to Drawing                                     |
|                           | Carton                     | W x H x D = TBD   |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |