

Fanless Panel PC Open Frame, 10.1" LCD monitor, 1280 x 800, LED 1000 nits, Intel® Celeron J1900



Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Atom Baytrail-M/D Chipset
- Intel® Celeron J1900
- Single Channel DDR3L 1333 MHz SDRAM
- 1 x HDMI, 1 x COM, 2 x USB, 2 x LAN

| | | |
|---------------------|----------------------------|---|
| Panel | Cell Type / Glass Surface | TFT LCD / Black Anti-Glare, low reflection coating |
| | Aspect Ratio / Size | Wide / 10.1" viewable diagonal area |
| | Active Area / Pixel Pitch | 216.96(H) x 135.6(V) mm / 0.1695(H) x 0.1695(V) mm |
| | Native Resolution / Colors | 1280(H) x 800(V) / 262 K |
| | Brightness / Contrast | 1000 cd/m ² (typ) / 500 : 1 |
| | Response Time | ≤ 16 ms |
| | Viewing Angle (typical) | H.130° (- 65° ~ + 65°) , V. 110°(- 60° ~ + 50°) |
| | Light Source | LED backlight, Long life, 35,000 hrs (typ) |
| System | CPU | Intel® Celeron J1900 |
| | BIOS | AMI |
| | System / Graphic Chipset | Intel® Atom Baytrail-M/D Chipset |
| | System Memory | Single Channel DDR3L 1333 MHz SDRAM |
| | HDD | 2 x SATA |
| | I/O port | 1 x HDMI |
| | | 2 x USB 3.0 |
| 1 x COM (RS232) | | |
| 2 x LAN | | |
| Expansion | 1 x Mini PCI-e | |
| Power | Power Input | 12V DC input with adapter |
| | Power Consumption | 28 Watt, <1 Watt |
| Operating Condition | Temperature / Humidity | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation) |
| Dimensions | Physical | Please refer to Drawing |
| | Carton | W x H x D = TBD |

| Options | Touch | Video / TV | Enhanced Panel | Others |
|---------|------------------|----------------------|--------------------------|------------------------------|
| | Resistive touch | SV + AV | Panel with LED backlight | Digital Signage(Stand alone) |
| | Capacitive touch | SV + AV + AV_Looping | High brightness panel | Networking Digital Signage |
| | SAW touch | SV + AV + TV | Wide Temperature | Motion Sensor |
| | Infrared touch | | Sunlight Readable | Light Sensor |
| | Protected glass | | | Auto-Dimming |