

Panel PC Open Frame, 15.6" LCD monitor, 1366 x 768, LED 1000 nits, Intel® Core i3 / i5 / i7 Processors



## Features

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Intel® Core i3 / i5 / i7 Processors
- Intel® H81
- DDR3 1600MHz, 2 x SO-DIMM, up to 16GB system memory
- 1 x VGA, 1 x HDMI, 3 x COM, 2 x LAN, 2 x USB 2.0, 2 x USB 3.0

|                           |                            |                                                         |
|---------------------------|----------------------------|---------------------------------------------------------|
| Panel                     | Cell Type / Glass Surface  | TFT LCD / Black Anti-Glare, low reflection coating      |
|                           | Aspect Ratio / Size        | Wide / 15.6" viewable diagonal area                     |
|                           | Active Area / Pixel Pitch  | 344.232(H) x 193.536(V) mm / 0.2588(H) x 0.2588(V) mm   |
|                           | Native Resolution / Colors | 1366(H) x 768(V) / 16.7M                                |
|                           | Brightness / Contrast      | 1000 cd/m <sup>2</sup> (typ) / 500 : 1                  |
|                           | Response Time              | ≤ 8 ms                                                  |
|                           | Viewing Angle (typical)    | H.90° (- 45° ~ + 45°) , V. 50°(- 30° ~ + 20°)           |
|                           | Light Source               | LED backlight, Long life, 35,000 hrs (typ)              |
| System                    | CPU                        | Intel® Core i3 / i5 / i7 Processors                     |
|                           | BIOS                       | UEFI                                                    |
|                           | System / Graphic Chipset   | Intel® HD Graphics (By CPU); Shared Memory              |
|                           | System Memory              | DDR3 1600MHz, 2 x SO-DIMM, up to 16GB system memory     |
|                           | HDD                        | 4 x SATA2                                               |
|                           | I/O port                   | 1 x VGA, 1 x HDMI                                       |
|                           |                            | 2 x USB 2.0, 2 x USB 3.0                                |
| 3 x COM (RS232/422/485)   |                            |                                                         |
| 2 x LAN, Mic-in, Line-out |                            |                                                         |
| Expansion                 | 1 x Mini PCI-e             |                                                         |
| Power                     | Power Input                | ATX PWR (24+4 pin)                                      |
|                           | Power Consumption          | 56 Watt, <1 Watt                                        |
| Operating Condition       | Temperature / Humidity     | 0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation) |
| Dimensions                | Physical                   | Please refer to Drawing                                 |
|                           | Carton                     | W x H x D = TBD                                         |

| Options | Touch            | Video / TV           | Enhanced Panel           | Others                       |
|---------|------------------|----------------------|--------------------------|------------------------------|
|         | Resistive touch  | SV + AV              | Panel with LED backlight | Digital Signage(Stand alone) |
|         | Capacitive touch | SV + AV + AV_Looping | High brightness panel    | Networking Digital Signage   |
|         | SAW touch        | SV + AV + TV         | Wide Temperature         | Motion Sensor                |
|         | Infrared touch   |                      | Sunlight Readable        | Light Sensor                 |
|         | Protected glass  |                      |                          | Auto-Dimming                 |